

Features

- Zero reverse recovery current
- Zero forward recovery voltage
- Temperature independent switching behavior
- High temperature operation
- High frequency operation

V_{RRM}	600V
$I_F (T_C = 143^\circ\text{C})$	4A
Q_c	10nC

Benefits


- Unipolar rectifier
- Substantially reduced switching losses
- No thermal run-away with parallel devices
- Reduced heat sink requirements

Applications


- SMPS, PFC
- Solar application, UPS, EV/HEV
- Motor drives, Wind turbine, Rail traction



TO-220ISO



Inner Circuit



G = GPT
3 = Gen3
S = SiC Schottky Diode
060 = Voltage Rating 600V
04 = Current Rating 4A
J = TO-220ISO
DDDDDD = Traceable Code



Maximum Ratings (at $T_j = 25\text{ }^\circ\text{C}$, unless otherwise specified)

Parameter	Symbol	Value	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	600	V
Surge Peak Reverse Voltage	V_{RSM}	600	V
Continuous Forward Current $T_c = 25^\circ\text{C}$ $T_c = 135^\circ\text{C}$ $T_c = 143^\circ\text{C}$	I_F	9.8 4.6 4	A
Repetitive Peak Forward Surge Current $T_c = 25^\circ\text{C}$, $t_p = 10\text{ms}$, Half Sine Pulse	I_{FRM}	20	A
Non-Repetitive Forward Surge Current $T_c = 25^\circ\text{C}$, $t_p = 10\text{ms}$, Half Sine Pulse	I_{FSM}	32	A
i^2t Value $T_c = 25^\circ\text{C}$, $t_p = 10\text{ms}$, Half Sine Pulse	$\int i^2 dt$	5.12	A^2s
Power Dissipation $T_c = 25^\circ\text{C}$ $T_c = 110^\circ\text{C}$	P_{tot}	38 16	W
Operating Junction Range	T_j	-55 to +175	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-55 to +175	$^\circ\text{C}$
Mounting Torque, M3 Screw	M	1	Nm

Electrical Characteristics (at $T_J = 25^\circ\text{C}$, unless otherwise specified)

Parameter	Symbol	Test Condition	Value			Unit
			min.	typ.	max.	
DC Blocking Voltage	V_{DC}		600	-	-	V
Forward Voltage	V_F	$I_F = 4\text{A}$ $T_J = 25^\circ\text{C}$	-	1.53	1.7	V
		$T_J = 175^\circ\text{C}$	-	1.94	2.5	
Reverse Current	I_R	$V_R = 600\text{V}$ $T_J = 25^\circ\text{C}$	-	0.05	50	μA
		$T_J = 175^\circ\text{C}$	-	0.44	100	
Total Capacitance	C	$f = 1\text{MHz}$ $V_R = 0\text{V}$	-	184	-	pF
		$V_R = 200\text{V}$	-	19.2	-	
		$V_R = 400\text{V}$	-	18.8	-	
Total Capacitive Charge	Q_C	$V_R = 400\text{V}$ $T_J = 25^\circ\text{C}$	-	10	-	nC
Capacitance Stored Energy	E_C	$V_R = 400\text{V}$	-	2	-	μJ

Thermal Characteristics

Parameter	Symbol	Test Condition	Value			Unit
			min.	typ.	max.	
Thermal Resistance, junction-case	$R_{th(j-c)}$		-	4	-	$^\circ\text{C/W}$

Typical Characteristics Curves




Figure 1. Forward Characteristics




Figure 2. Reverse Characteristics




Figure 3. Power Derating




Figure 4. Current Derating

Typical Characteristics Curves




Figure 5. Capacitance vs. Reverse Voltage




Figure 6. Reverse Charge vs. Reverse Voltage




Figure 7. Capacitance Stored Energy





Figure 8. Transient Thermal Impedance

Package Dimensions



DIM.	Unit(mm)		Unit(inch)	
	Min	Max	Min	Max
A	9.7	10.4	0.381	0.409
B	2.5	3	0.098	0.118
C	3.5	3.9	0.137	0.153
D	0.7	0.92	0.027	0.036
E	3.72	3.95	0.146	0.155
F	14.51	15.55	0.571	0.612
G	12.95	13.9	0.509	0.547
H	4.95	5.19	0.194	0.204
I	4.38	4.65	0.172	0.183
J	1.15	1.36	0.045	0.053
K	5.86	6.38	0.230	0.251
L	2.35	2.85	0.092	0.112
M	0.32	0.58	0.012	0.022
N	1.18	1.42	0.046	0.055

Ordering Information

Part Number	Marking	Package	Packaging Mode
G3S06004J	G3S06004J	TO-220ISO	50pcs/Tube